



Telescopic Gate



TSG Series



Ideal Fencing
and Gates
is proud to
be serving
industry
since 2004.

For over (20) years the company has been manufacturing Telescopic Gates for commercial and industrial use, setting the pace with innovative design and proven product excellence.

Ideal Fencing and Gates manufactures a comprehensive range of Telescopic Gates for all commercial and industrial applications including;

- Factories
- Warehouses
- Distribution Centres
- Carpark Entrances
- Loading Docks
- Sporting Complexes
- Local and State Government Projects
- Schools and other Education facilities

We use computer aided design programs extensively in our research and development process seeking to improve the strength and efficiency in our product offering.

We make to measure to ensure correct fit and that installation on site is completed quickly and efficiently.

Don't hesitate to contact Ideal Fencing and Gates sales staff to discuss your specific application requirements.

THE IDEAL
ADVANTAGE

SPECIFICATIONS

TSG Series

Sub Frame

Gate structure is manufactured from pre-galvanised steel SHS/RHS sections.

Material thickness is dependent on the opening width and the security requirements of the project.

Size

Refer to the table below.

Height of gate to suit fence line: standard heights 1800mm– 2400mm, higher if required.

Gate Infill

Infill typically vertical bar utilising 25mm SHS. A range of other options are available including palisade, RHS, angles, bar configuration, weld mesh, cladding or a bespoke finish to suit specific site requirements.

Automation

Automation is provided via high duty electro-mechanical gate operator.

Safety supplied as standard with in built obstacle detection, dual height and dual side photo-electrical beams, flashing light and warning sign.

A range of control options are available including access control, radio control or Vehicle detection loop system.

Finish Options

- Galvabond steel (standard).
- Dulux Duralloy or Interpon D1000 powdercoat finishes are suitable.
- Electro-static twin coat wet sprayed paint.

Special Notes

- The power supply required for the motor is either:
 - Single phase hard wired (10 amp), located within one metre of the motor.
 - Low voltage 24v wired supply, within one metre of the motor.
 - 24v High efficiency solar power.
- Work by others:
 - Power supply provision if required.
 - Structurally adequate footings / mounting points to support the gate.
- Product warranty – 12 months.

Comparison

	TSG100	TSG200	TSG300
Maximum Gate Width	8,000mm	15,000mm	30,000mm
Additional Frame Detail Leaf Overlap	600mm	900mm	1,200mm – 2,400mm

Get in touch today to discuss your specific requirements.

IDEAL

FENCING & GATES



Get in Touch

📍 3 Narang Place
St Marys, NSW 2756

✉️ nswsales@idealgates.com.au

☎️ +61 2 9675 4448

📍 8 Bessemer Road
Bayswater, North VIC 3153

✉️ vicsales@idealgates.com.au

☎️ +61 3 8720 9400

💻 www.idealgates.com.au